



SEAM GRIP®

Seam Sealer for Outdoor Gear

- Seals the seams on tents, tarps, backpacks, rainwear
- Permanently patches holes and repairs tears
- Washable and unaffected by extreme cold or heat
- One tube seals the critical seams on an average 2-person tent

Note: For silicone-treated tent and tarp fabrics, use SilNet™ Silicone Seam Sealer and Sil Fix™ Adhesive.

One of more than 100 Care and Repair products from Gear Aid.

DIRECTIONS: SEAM SEALING

PREP: Clean seams on used tents with isopropyl (rubbing) alcohol.

APPLY: Apply a thin film of Seam Grip to inside of the seam (one coat).

DRY: Let dry overnight (approximately 8-12 hours—may be longer in low humidity). For 2-hour dry time, mix small batches of Seam Grip with CotoI-240™. Apply with brush.

ADHESIVE APPLICATIONS: Roughen and clean surfaces with rubbing alcohol. Apply Seam Grip to both surfaces. Allow to dry (cure) 15 minutes, then join (clamp or tape) surfaces together overnight.

CLEAN UP: Seam Grip will dry (cure) and flake off hands. Washing hands in soap and water will accelerate curing. Uncured Seam Grip can be partially removed with a coarse cloth soaked in rubbing alcohol. For easiest clean up wear disposable rubber gloves.

STORAGE: Advance contents to tube neck and replace original cap securely. Store partially used tube in freezer.

DISCLAIMER: Since use of this material is beyond our control, we make no express or implied warranty.

CAUTION: VAPOR HARMFUL, FLAMMABLE CONTAINS TOLUENE. Use only in well ventilated area. Keep away from heat and open flame. Avoid prolonged contact with skin. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: Using this product will expose you to Toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

SPECIAL APPLICATIONS & TIPS

TENT SEAM SEALING: Perimeter seams on 'seam taped' tents are often not factory sealed and require sealing. Apply a thin film of Seam Grip to inside floor seams (Fig. 1). Allow to dry (cure) overnight. A slight surface tack is normal and will dissipate with tent use.

Use Seam Grip to seal areas that regularly leak, such as stake-out points at corners (Fig. 2).

To seal the seams on your rainfly, set it up inside-out for easier application. Attach the rainfly to the tent so all seams are taut (Fig. 3).

TEAR & HOLE REPAIRS: Apply just enough Seam Grip to cover the hole and spread 1/4 inch beyond. Allow to dry (cure) level overnight. For 2 hour cure time, mix Seam Grip with CotoI-240™ before applying. (Fig. 4)

SEAM TAPE TIP: If a small section has peeled use Seam Grip to re-attach it (Fig. 5). If the tape seems to be failing everywhere, remove and discard it, then clean the seams with isopropyl alcohol and re-seal with Seam Grip.

FIGURE 1




FIGURE 2



FIGURE 3



FIGURE 4



FIGURE 5



McNETT
CORPORATION

1411 Meador Ave.
Bellingham, WA 98229-5845
www.mcnett.com | MADE IN USA

Gear Aid™, Seam Grip®, CotoI-240™, Sil Fix™ and SilNet™ are trademarks of McNett Corporation. Copyright 2010 McNett Corporation. NSN 8040-01-458-2768

For more repair
& care tips, check out
www.gear-aid.com



RECYCLABLE